



# MOJO

12V SPOTLIGHTS

location:  
**DRY**

## SPECIFICATIONS:

### DESCRIPTION

Low voltage spotlight with handcrafted glass. Includes Quick-Connect jack.

### LAMPING

**Standard:** 50W Shielded flood 12V halogen MR16 lamp, included.

**LED:** 9W Replaceable 12V LED MR16 Flood, dimmable, 90+ CRI, 3000°K CCT, 670 lumens, 25,000 hours, lamp included.

### QUICK-CONNECT JACK

Integral Quick-Connect jack is compatible with Besa Rail Adapter.

### ELEMENT OPTIONS

Available as either a Quick-Connect element only or with Rail Adapter for use with Besa Monorail. Longer stem options are also available.

### METAL FINISH


Available in Bronze or Satin Nickel.

### LABELS

UL or ETL Listed. Suitable for Dry Locations (interior use only).



MOJO IN BRONZE & SATIN NICKEL W/ LED OPTION



## SPOTLIGHT OPTIONS:

### SP SPOTLIGHT ELEMENT ONLY



- Spotlight Fixture with Shade
- Quick-Connect Jack integral
- Compatible with Besa Canopies and Rail Adapter

### RSP SPOTLIGHT + RAIL ADAPTER



#### READY FOR RAIL

- Spotlight Fixture with Shade, plus Rail Adapter
- Quick-Connect Jack integral
- Compatible with Besa Monorail System

## ORDERING:

| QUICK-CONNECT  | SHADE OPTIONS       | LAMP OPTIONS              | STEM OPTIONS              | METAL FINISH    |
|----------------|---------------------|---------------------------|---------------------------|-----------------|
| SP Jack Only   | MOJOMB Metal Bronze | (blank) 50W Hal MR16      | (blank) Standard          | BR Bronze       |
| RSP Rail-Ready | MOJOMN Metal Nickel | LED 9W LED MR16, dimmable | 06 6"<br>12 12"<br>18 18" | SN Satin Nickel |

**Ex. 1SP-MOJOMN-SN**  
Mojo Spotlight w/ Metal Nickel Shade,  
Satin Nickel Finish

Project Information:


## Longer Stem Options

Besa spotlights have a standard stem 1.5" long. For a spotlight with a longer drop, order a stem length of 6", 12" or 18".

Not suitable for use on sloped ceiling when spotlight is installed on a quick-connect canopy.

**Note: These are NOT field installable. The complete unit is built at the factory.**

- Available options are
- SP06** 6" stem adds 3.625" to overall length
  - SP12** 12" stem adds 9.625" to overall length
  - SP18** 18" stem adds 15.625" to overall length



All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/22