



SURFACE POWER SUPPLIES

12V MONORAIL

location:
DRY

SPECIFICATIONS:

DESCRIPTION

Canopy-style surface-mount transformers. Electronic transformers provide 12V AC power. Includes 2' of 10AWG Flexible Feed Cable. 120V input.

60W & 105W Electronic Low-profile LED rail power supply, specifically for use with LED spotlights and pendants, supports up to (9) 6W max LED spotlights or pendants. No-load 12V dimmable electronic transformer fits in the junction box. No remote transformer required. Not recommended for standard halogen-lamped items

DIMMING

Besa electronic surface transformers are compatible with low voltage electronic dimmers.

COMPATIBILITY

Compatible with Besa 12V Monorail rail.

METAL FINISH

Available in Black or Satin Nickel.

LABELS

UL or ETL Listed. Suitable for Dry Locations (interior use only).

60W Electronic LED Low-Profile

5" Dia. x 0.75" H,
overall height with rail connector 2.0"

R12-SA60LED-BK	60W Black, 120V
R12-SA60LED-BK-DIM010	60W Black, 0-10V Dimming
R12-SA60LED-SN	60W Satin Nickel, 120V
R12-SA60LED-SN-DIM010	60W Satin Nickel, 0-10V Dimming
R12-SA105LED-BK	105W Black, 120V
R12-SA105LED-BK-DIM010	105W Black, 0-10V Dimming
R12-SA105LED-SN	105W Satin Nickel, 120V
R12-SA105LED-SN-DIM010	105W Satin Nickel, 0-10V Dimming



Project Information:

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 5/24