POGO

12V MINI PENDANTS

location **DRY**

SPECIFICATIONS:

DESCRIPTION

Low voltage mini pendant with handcrafted glass.

LAMPING

Standard: 50W MAX GY6.35 base, T-shape lamp. Dimmable with ELV Dimmer (not included).

LED: 5W Replaceable 12V LED, dimmable, 90+ CRI, 3000°K CCT, 550 lumens, 25,000 hours. Lamp included. Dimmable with ELV Dimmer (not included).

DIEELISE

Inner Shade shall be handcrafted glass of Opal Matte.

Outer Shade shall be handcrafted glass of various decors, with various foil interior decors.

Length of 6.25" and height of 6.25" and depth of 4"

Opening sizes: 24mm top.

CORD

Standard cord is 10' field-adjustable coaxial type with teflon jacket and decorative sleeve at the socketholder. Jacket tint coordinates with metal finish. Cords also available in 15' lengths.

STANDARD PENDANT (1XC, 1XT, X)

Mini pendant comes complete with either dome-style or flat-style canopy. See next page for multi light options with "X" prefix.

QUICK-CONNECT OPTION (XP, RXP)

Quick-Connect Jack is compatible with Besa Rail Adapter.

METAL FINISH


Glass retainer hardware, sleeve and Quick-Connect Jack and/or canopies are finished in either Black, Bronze or Satin Nickel.


MOUNTING

Installs directly to a 4" octagonal ceiling box. Suitable for sloped ceilings.

LABELS

UL or ETL Listed. Suitable for Dry Locations (interior use only).







POGO SHOWN IN WHITE/INNER SILVER (4293SF) & BLACK/INNER GOLD (4293GF)



For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 9/24



ORDERING:

CONNECTION	- SHADE OPTIONS	- LAMP OPTIONS	- METAL FINISH -	OPTIONS
Quick-Connect	4293GG Gold/Inner Gold Foil	(blank) Bipin socket	BK Black	L 15' cord
XP Jack Only	4293GF Black/Inner Gold Foil	LED 5W LED	BR Bronze	277 277V
RXP Rail-Ready	4293SF White/Inner Silver Foil		SN Satin	DIM010 0-10V
	4293SS Silver/Inner Silver Foil		Nickel	Dimming
Pendant Fixtures				

1XC Dome Canopy 1XT Flat Canopy

Multi liaht

X For Multi light Canopy



Ex. 1XT-4293GF-SN

Pogo Pendant w/ Black/Inner Gold Glass Shade, Satin Nickel Finish


MULTIPORT CANOPY OPTIONS FOR CORD PENDANTS

T23X 3 LIGHT ROUND CANOPY




- Suitable for sloped ceilings
- Black, Bronze or Satin Nickel
- 10" Dia. shades MAX, with staggered heights
- * For larger diameter glasses, Skyhooks are required for spacing

T23XL 3 LIGHT LARGE ROUND CANOPY



- Suitable for sloped ceilings
- · Black, Bronze or Satin Nickel
- 16" Dia. shades MAX, with staggered heights
- * For larger diameter glasses, Skyhooks are required for spacing


T26X 6 LIGHT ROUND CANOPY



- Suitable for sloped ceilings
- Black, Bronze or Satin Nickel 10" Dia. shades
- MAX, with staggered heights * For larger diameter glasses, Skyhooks are required for

spacing

T29X 9 LIGHT ROUND CANOPY



- Suitable for sloped ceilings
- Black, Bronze or Satin Nickel
- 10" Dia. shades MAX, with staggered heights
- For larger diameter glasses, Skyhooks are required for spacing

QUICK-CONNECT OPTIONS:

XP PENDANT ELEMENT ONLY



- · Pendant Shade and Cord/Socket Set
- 10' Field-adjustable braided coaxial-type cord with a teflon jacket (clear or bronze tint coordinates with metal finish)
- Quick-Connect Jack provided
- Compatible with Besa Canonies and Bail Adapter
- · Black, Bronze or Satin Nickel metal finishes

RXP PENDANT + RAIL ADAPTER




READY FOR RAIL

- Pendant Shade and Cord/Socket Set, plus Rail Adapter
- 10' Field-adjustable braided coaxial-type cord with a teflon jacket (clear or bronze tint coordinates with metal finish)
- Quick-Connect Jack provided
- · Compatible with Besa Monorail System
- · Black, Bronze or Satin Nickel metal finishes

24" · Suitable for sloped ceilings

T285 8 LIGHT SQUARE CANOPY



- Black, Bronze or Satin Nickel
- 20" Dia, shades MAX, with staggered heights
- * For larger diameter glasses, Skyhooks are required for spacing

FIXED PENDANT OPTIONS:


1XC 1 LIGHT PENDANT, DOME CANOPY



NO CORD CUTTING REQUIRED

- Suitable for use on sloped ceilings
- 1x electronic 60W dimmable 120V transformer
- Installs to standard 4" octagonal junction box
- · Black, Bronze or Satin Nickel metal finishes

T23V 3 LIGHT BAR CANOPY



- · Suitable for sloped ceilings
- Black, Bronze or Satin Nickel
- 20" Dia. shades MAX, with staggered heights
- * For larger diameter glasses, Skyhooks are required for spacing


1XT 1 LIGHT PENDANT, FLAT CANOPY



- Suitable for use on sloped ceilings
- 1x electronic 60W dimmable 120V transformer, fits partially in iunction box
- · Installs to standard 4" octagonal junction box
- · Black, Bronze or Satin Nickel metal finishes

T27V 7 LIGHT BAR CANOPY

T24V 4 LIGHT BAR CANOPY



- Suitable for sloped ceilings
- · Black, Bronze or Satin Nickel

 Suitable for sloped ceilings · Black, Bronze or Satin Nickel

- 20" Dia. shades MAX, with staggered heights
- * For larger diameter glasses, Skyhooks are required for spacing

• 20" Dia. shades MAX, with staggered heights

* For larger diameter glasses, Skyhooks are required for spacing

X 1 LIGHT PENDANT FOR MULTIPORT CANOPIES



- · Suitable for use on sloped ceilings
- 1x electronic 60W dimmable 120V transformer, fits partially in
- Installs to standard 4" octagonal junction box
- · Black, Bronze or Satin Nickel metal finishes

ADDITIONAL OPTIONS:

277V:

For 277V option, add an "277" to the end of the item number, i.e. 1XT-174352-SN-277.

0-10V Dimmina:

For 0-10V Dimming option, add an "DIM010" to the end of the item number, i.e. 1XT-174352-SN-DIM010.

15Ft. CORD LENGTH:

For longer 15' cord, add an "L" to the end of the item number, i.e. 1XT-174352-SNL.

HOW TO ORDER A MULTILIGHT FIXTURE

Order your canopy with the selected 12V multi light pendants (indicated by "X" prefix) for the complete fixture:

Example: 1x T23XL-LED-SN (3 Light Large Round LED Canopy)

1x X-4293GG-SN (Pogo Pendant in Gold/Inner Gold Foil)

1x X-4293GF-SN (Pogo Pendant in Black/Inner Gold Foil)

1x X-4293GG-SN (Pogo Pendant in Gold/Inner Gold Foil)