

WILLOW

12V MINI PENDANTS

SPECIFICATIONS:

DESCRIPTION

Low voltage mini pendant with handcrafted glass.

LAMPING

LED: 3W Replaceable 12V LED MR11, dimmable, 80+ CRI, 3000°K CCT, 200 lumens, 25,000 hours. Lamp included. Dimmable with ELV Dimmer (not included).

DIFFUSER

Shade shall be handcrafted glass of Clear decor. Diameter of 3.5" and height of 13.75" **Opening sizes:** 64mm min. (top), 45.5mm min. (bottom)

CORD

Standard cord is 10' field-adjustable coaxial type with teflon jacket and decorative sleeve at the socketholder. Jacket tint coordinates with metal finish. Cords also available in 15' lengths.

STANDARD PENDANT (1XT, X)

Mini pendant comes complete with a flat-style canopy. See next page for multi light options with "X" prefix.

QUICK-CONNECT OPTION (XP, RXP)

Quick-Connect Jack is compatible with Besa Rail Adapter.

METAL FINISH

Glass retainer hardware, sleeve and Quick-Connect Jack and/or canopies are finished in either Black or Satin Nickel.

MOUNTING

Installs directly to a 4" octagonal ceiling box. Suitable for sloped ceilings.

LABELS

UL or ETL Listed. Suitable for Dry Locations (interior use only).

Project Information:

For ordering information, see next page

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.



1688WW (WILLOW) IN SATIN NICKEL & BLACK

*Shown with customizable accents

location DRY



REV 9/24



WILLOW

12V MINI PENDANTS

Suitable for sloped ceilings

Black, Bronze or Satin Nickel

• 16" Dia. shades MAX, with staggered heights

* For larger diameter glasses, Skyhooks are required for spacing

Suitable for sloped ceilings

Black, Bronze or Satin Nickel

• 10" Dia. shades MAX, with staggered heights


spacing

* For larger diameter glasses, Skyhooks are required for

T23XL 3 LIGHT LARGE ROUND CANOPY

ORDERING:

ORDERING:					MULTIPOR	T CANOPY	OPTION	S FOR CORD PENDANTS	
CONNECTION	- GLASS OPTIONS - LA	AMP OPTIONS -	METAL FINISH	OPTIONS	T23X 3 LIGHT	ROUND CANC	OPY	T23XL 3 LIGHT LARGE ROUND	C/
Quick-Connect XP Jack Only RXP Rail-Ready	1688WW Crystal Rods LE	ED 3W LED	BK Black SN Satin Nickel	L 15' cord 277 277V DIM010 0-10V Dimming	8"]1.25″	aad		fo
Pendant Fixtures 1XT Flat Canopy Multi light X For Multi light Canopy Y Y Y	Ex. 1XT-1688WW-LED-SN Multilight Willow LED Mini Pendant w/ Clear-Crystal Rods X For Multilight Satin Nickel Finish			Crystal Rods,	 Suitable for sloped ceilings Black, Bronze or Satin Nickel 10" Dia. shades MAX, with staggered heights * For larger diameter glasses, Skyhooks are required for spacing 			 Suitable fo Black, Bron Black, Bron 16" Dia. sha; staggered h For larger glasses, Sl are require 	
Multilight Canopies Available, see options on right.					13"	ROUND CANC			,
					0	• Blac Sat • 10" MA sta * For gla are	ck, Bronze or in Nickel Dia. shades X, with ggered heights r larger diamete seses, Skyhooks r required for acing	$r \qquad \bigcirc $	r Di AX, agg
	ECT OPTIONS:				T285 8 LIGH	T SQUARE CAN		2 1 1 10	_
RXP PENDANT EL	Pendant Shade and Cord, 10' Field-adjustable braidi or bronze tint coordinate: Quick-Connect Jack provi Compatible with Besa Cai Black, Bronze or Satin Nic HAIL ADAPTER READY FOR RAIL Pendant Shade and Cord, 10' Field-adjustable braidi	ed coaxial-type s with metal fin ided nopies and Rail kel metal finish /Socket Set, plu	ish) Adapter ies is Rail Adapter		0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	0	 Black, Br 20" Dia. 5 * For larg required 1 	for sloped ceilings onze or Satin Nickel shades MAX, with staggered heights er diameter glasses, Skyhooks are for spacing	
	or bronze tint coordinate: • Quick-Connect Jack provi • Compatible with Besa Mc • Black, Bronze or Satin Nic	s with metal fin ided pnorail System	iish)		33. 	75″	• S 1.75" • B 4.75" • 2 * F	iuitable for sloped ceilings Black, Bronze or Satin Nickel 10° Dia. shades MAX, with staggered heights For larger diameter glasses, Skyhooks are required for spacing	
FIXED PENDA	INT OPTIONS:				T24V 4 LIGH	IT BAR CANOP			
1XT 1 LIGHT PE	NDANT, FLAT CANOP • Suitable for use on sloped • 1x electronic 60W dimma junction box • Installs to standard 4" oct • Black, Bronze or Satin Nic	d ceilings Ible 120V transf agonal junctior	n box	in	• • • 10.75″ •	43" • IT BAR CANOP	[1.75" • B • 2 • [4.75" * F	uitable for sloped ceilings Black, Bronze or Satin Nickel 10" Dia. shades MAX, with staggered heights For larger diameter glasses, Skyhooks are equired for spacing	5
X 1 LIGHT PEND	DANT FOR MULTIPORT • Suitable for use on sloped • 1x electronic 60W dimma junction box • Installs to standard 4" oct • Black, Bronze or Satin Nic	d ceilings able 120V transf agonal junctior	n box	in	• 11"	43" • • • • • • • • • • • • • • • • • • •	• S [1.75" • B • 2 • F	iuitable for sloped ceilings black, Bronze or Satin Nickel 10° Dia. shades MAX, with staggered heights For larger diameter glasses, Skyhooks are required for spacing	 5
ADDITIONAL	OPTIONS:							IGHT FIXTURE	
0-10V Dimming:	d an " 277 " to the end of th			SN- 277 .	by "X" pref Example:	ix) for the com 1x T23XL-LEE	nplete fixtur D-SN (3 Light	t Large Round LED Canopy)	
For 0-10V Dimming i.e. 1XT-174352-SN-	option, add an " DIM010 " t DIM010 .	to the end of t	ne item number,					Villow LED Pendant with Crystal R Villow LED Pendant with Crystal R	



shades MAX, with staggered heights ger diameter glasses, Skyhooks are for spacing

- Suitable for sloped ceilings
- Black, Bronze or Satin Nickel
- 20" Dia. shades MAX, with staggered heights For larger diameter glasses, Skyhooks are required for spacing

IGHT FIXTURE

- nt Large Round LED Canopy)
 - Willow LED Pendant with Crystal Rods) 1x X-1688WW-LED-SN (Willow LED Pendant with Crystal Rods)
 - 1x X-1688WW-LED-SN (Willow LED Pendant with Crystal Rods)

QUICK-C

XP PEND



RXP PENI

FIXED P

1XT 1 LIG

5* 0.625* 10' 10'	 Suitable for use on sloped ceilings 1x electronic 60W dimmable 120V transformer, fits partia junction box Installs to standard 4" octagonal junction box Black, Bronze or Satin Nickel metal finishes
	the sector of the sector

X 1 LIGHT

277V:

0-10V Dimr

15Ft. CORD LENGTH:

For longer 15' cord, add an "L" to the end of the item number, i.e. 1XT-174352-SNL.