

## TOPPER 12

FLUSH MOUNT CEILING

location:

## **SPECIFICATIONS:**

### **DESCRIPTION**

Flush-mounted ceiling fixture, featuring fused 3-piece glass diffuser.

#### LAMPING

**LED:** 16W Integrated source, 120V, CL dimmable, 85+ CRI, 3000°K CCT, 1500 lumens, 30,000 hours, included.

#### DIFFUSER

Handcrafted glass diffuser in Opal Glossy with clear or smoke trim. 12" Dia. x 3" H

## **CONSTRUCTION**


Stamped aluminum fitter is powder coated white.

### **MOUNTING**

Installs directly to a 4" octagonal outlet box, centered on fixture. 90°C supply wire required for incandescent lamping.

#### LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).





OPAL/SMOKE (TOPPER12SMC)

#### TOPPER12CLC OPAL/CLEAR



## **ORDERING:**

 FIXTURE/DECOR
 LAMP OPTIONS

 TOPPER12CLC
 12"Dia. Opal/Clear
 LED 16W LED,

 TOPPER12SMC
 12"Dia. Opal/Smoke
 1500 lumens

# Ex. TOPPER12CLC-LED Tonner 12 (eiling, Onal/Clear S

Topper 12 Ceiling, Opal/Clear Stone Glass Shade

Project Information:		

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

**REV 10/24**