



TUCA 15 / 19

FLUSH MOUNT CEILING

location:
DAMP

SPECIFICATIONS:

DESCRIPTION

Flush-mounted ceiling fixture, featuring handcrafted glass diffuser.

LAMPING

LED: 20W Integrated source, 120V, CL dimmable, 90+ CRI, 3000°K CCT, 2000 lumens, 30,000 hours, included. (For Tuca 15 only)

LED: 30W Integrated source, 120V, CL dimmable, 90+ CRI, 3000°K CCT, 3000 lumens, 30,000 hours, included. (For Tuca 19 only)

DIFFUSER

Handcrafted glass diffuser in Opal Matte with metallic foil ring.

Tuca 15: 15.5" Dia. x 3.25" H

Tuca 19: 19.25" Dia. x 3.5" H

CONSTRUCTION

Glass diffuser is secured to fitter with "twist & lock" bayonet action. Stamped aluminum fitter is powder coated white.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture.

90°C supply wire required for incandescent lamping.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



OPAL/SILVER FOIL (TUCA19SFC)

TUCA15GFC
OPAL/GOLD FOIL



For ordering information, see next page


All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/24




ORDERING:

Tuca 15: _____



FIXTURE/DECOR	-	LAMP OPTIONS
TUCA15GFC 15.75" Opal/Gold Foil		LED 20W LED,
TUCA15SFC 15.75" Opal/Silver Foil		2000 lumens

Tuca 19: _____



FIXTURE/DECOR	-	LAMP OPTIONS
TUCA19GFC 19.25" Opal/Gold Foil		LED 30W LED,
TUCA19SFC 19.25" Opal/Silver Foil		3000 lumens

Ex. TUCA15GFC-LED
Tuca 15 Ceiling, Opal/Gold Foil
Glass Shade

Project Information: