

VIVA 13 / 16

FLUSH MOUNT CEILING

location:

SPECIFICATIONS:

DESCRIPTION

Flush-mounted ceiling fixture, featuring Opal glass with patterned Clear center diffuser.

LAMPING

LED: 20W Integrated source, 120V, CL dimmable, 90+ CRI, 3000°K CCT, 2000 lumens, 30,000 hours, included. (Viva 13 only)

LED: 30W Integrated source, 120V, CL dimmable, 90+ CRI, 3000°K CCT, 3000 lumens, 30,000 hours, included. (Viva 16 only)

DIFFUSER

Handcrafted glass diffuser in Opal with patterned Clear center .

Viva 13: 13" Dia. x 4" H **Viva 16:** 16" Dia. x 4.5" H

CONSTRUCTION

Glass diffuser is secured to fitter with "twist & lock" bayonet action. Stamped aluminum fitter is powder coated white.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture. 90°C supply wire required for incandescent lamping.

IARFIS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



OPAL/CLEAR


Project Inform	ation:		


All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/24



ORDERING:





Ex. VIVA13C-LEDViva 13 Ceiling, Opal/Clear Glass Shade

Project Information: