



KATIE 10 / 12

FLUSH MOUNT CEILING

location:
DAMP

SPECIFICATIONS:

DESCRIPTION

Flush-mounted round ceiling luminaires, featuring handcrafted glass. Two sizes available.

LAMPING

Standard: 60W MAX E26 base A19, 120V, lamp not included. Dimmable with standard incandescent dimmer (not included).

LED: 15W Integrated source, 120V, CL dimmable, 90+ CRI, 3000°K CCT, 1500 lumens, 50,000 hours, included. (For Katie 10 only)

LED: 20W Integrated source, 120V, CL dimmable, 90+ CRI, 3000°K CCT, 2000 lumens, 50,000 hours, included. (For Katie 12 only)

DIFFUSER

Handcrafted ribbed glass diffuser is available in Opal Matte decor.

Katie 10 #945107: 10.5" Dia. x 3.75" H

Katie 12 #945007: 12" Dia. x 4.5" H

CONSTRUCTION

Glass diffuser is secured to fitter with three set screws.

Stamped aluminum fitter is powder coated white.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture.

90°C supply wire required for incandescent lamping.


LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).




KATIE CEILING SHOWN IN OPAL MATTE

Katie 10: #9451



Katie 12: #9450



FIXTURE/DECOR	LAMP OPTIONS	OPTIONS
945107C 10.5" Dia. Opal Matte	(blank) 1x 60W A19 Incan LED 15W LED, 1500 lumens	LW Low Wattage labeling

FIXTURE/DECOR	LAMP OPTIONS	OPTIONS
945007C 12.0" Dia. Opal Matte	(blank) 2x 60W A19 Incan LED 20W LED, 2000 lumens	LW Low Wattage labeling

Ex. 945007C

Katie 12 Ceiling w/ Opal Matte Glass Shade

Project Information:

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.