

LIDO

VANITIES WALL

location:

SPECIFICATIONS:

DESCRIPTION

1-3 Light vanity luminaires featuring handcrafted glass.

Standard: 60W E26 base A19, 120V, lamp not included. Dimmable with standard incandescent dimmer (not included).

LED: 9W Replaceable source, 120V, dimmable, 90+ CRI, 3000°K CCT, 800 lumens, 30,000 hours. Lamp included.

DIFFUSER

Handcrafted glass diffuser in Opal Matte.

CONSTRUCTION

Canopy and oval faceplate (7.5" x 4.75" H) are plated steel. Lampholders are stamped steel, on 0.5" square steel tubing, with plated finish.

METAL FINISH

Fixture shall be finished in Bronze, Chrome or Satin Nickel.

MOUNTING

Installs directly to a 4" octagonal outlet box. Wall-mount only. Glass diffuser can be oriented upward or downward.

UL or ETL Listed. Suitable for Damp Locations (interior use only).



*Glass shades can be installed vertically on adjustable fitter




LIDO SHOWN IN OPAL MATTE (888607)

ORDERING:

FIXTURE -	SHADE OPTIONS	- LAMP OPTIONS	- METAL FINISH
1WT Sconce	888607 Opal Matte	(blank) 60W A19	CR Chrome
2WT 2-Light		LED 9W LED 120V,	SN Satin Nickel
3WT 3-Light		dimmable	

Ex. 2WT-888607-CR Lido 2-Light Vanity, Opal Matte, Chrome Finish





All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/24