



POGO

VANITIES WALL



location: DAMP

SPECIFICATIONS:

DESCRIPTION

2-3 Light ADA-compliant vanity luminaires featuring handcrafted glass.

LAMPING

Standard: 60W G9 Bi-pin socket, 120V, suitable for dimming. Lamp included.

LED: 5W Replaceable source, 120V, dimmable, 90+ CRI, 3000° K CCT, 450 lumens, 25,000 hours, lamp included.

DIFFUSER

Glass diffusers available in various decors.

4.5" L x 4.5" H, spaced 7.875" on center.

CONSTRUCTION

Rectangular canopy (4.75" x 5.5" H) and lampholder are stamped steel, with plated finish.

METAL FINISH

Fixture shall be finished in Satin Nickel.

MOUNTING

Installs directly to a 4" octagonal outlet box, with up to 1" offset.

Orient horizontal or vertical, wall-mount only.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



POGO SHOWN IN OPAL GLOSSY (718006)

7180GF
BLACK/INNER GOLD

7180SF
WHITE/INNER SILVER



ORDERING:

FIXTURE	SHADE OPTION	LAMPING OPTIONS	METAL FINISH
2WS 2 Light	718006 Opal Glossy	(blank) 60W G9 Socket	SN Satin Nickel
3WS 3 Light	7180GF Black/Inner Gold	LED 5W LED 120V, dimmable	
	7180SF White/Inner Silver		

Ex. 3WS-718006-SN
Pogo Vanity w/ Opal Glossy Glass Shade, Satin Nickel Finish

2WS: 14.625" L x 5.5" H x 6.25" D



3WS: 22.5" L x 5.5" H x 6.25" D



Project Information:

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/24