



PAOLO

VANITIES WALL



SPECIFICATIONS:

DESCRIPTION

2-3 Light **ADA-compliant** vanity luminaires featuring handcrafted glass.

LAMPING

Standard: 50W G9 Bi-pin socket, 120V, suitable for dimming. Lamp included.

LED: 5W Replaceable source, 120V, dimmable, 90+ CRI, 3000° K CCT, 450 lumens, 25,000 hours, lamp included.

DIFFUSER

Glass diffusers available in various decors. 4.25" x 4.25" H, spaced 7.875" on center.

CONSTRUCTION

Rectangular canopy (4.75" x 5.5" H) and lampholder are stamped steel, with plated finish.

METAL FINISH

Fixture shall be finished in Satin Nickel.

MOUNTING

Installs directly to a 4" octagonal outlet box, with up to 1" offset. Orient horizontal or vertical, wall-mount only.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



PAOLO SHOWN IN GLITTER (7873GL)

787307
OPAL MATTE

787319
CARRERA

787399
OPAL-FROST

78735T
STUCCO



For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/24



ORDERING:

FIXTURE	SHADE OPTION	LAMPING OPTIONS	METAL FINISH
2WS 2 Light	787307 Opal Matte	(blank) 50W G9 Socket	SN Satin Nickel
3WS 3 Light	787319 Carrera	LED 5W LED 120V, dimmmable	
	787399 Opal-Frost		
	7873GL Glitter		
	7873ST Stucco		
Ex. 3WS-787319-SN			
Paolo Vanity w/ Carrera Glass Shade, Satin Nickel Finish			

2WS: 14.625" L x 4.75" H x 4" D



3WS: 22.5" L x 4.75" H x 4" D



Project Information: