



**PALLA 5**

VANITIES WALL

location:  
**DAMP**

**SPECIFICATIONS:**

**DESCRIPTION**

2-3 light vanity luminaires featuring handcrafted glass.

**LAMPING**

**Standard:** 40W G9 Bi-pin base, 120V, lamp included. Suitable for use in an open fixture. Dimmable with standard incandescent dimmer (not included).

**LED:** 5W Replaceable source, 120V, dimmable, 90+ CRI, 3000° K CCT, 450 lumens, 25,000 hours, lamp included.

**DIFFUSER**

Shade shall be handcrafted glass of various decors.  
4.75" Dia. x 3.875" H, spaced 7.875" apart on center.

**CONSTRUCTION**

Fixture utilizes metal arm assembly and stamped steel body, with plated finish. Decorative finials can be removed for downlighting applications. Decorative outlet box cover optional when not required.

**METAL FINISH**

Fixture shall be finished in Bronze or Satin Nickel.

**MOUNTING**

Installs directly to a 4" octagonal outlet box, with 1.75" left or right offset. Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

**LABELS**

UL or ETL Listed. Suitable for Damp Locations (interior use only).



PALLA 5 SHOWN IN OPAL MATTE (565807)

565819  
CARRERA



**For ordering information, see next page**

All dimensions provided are nominal.  
Allowance must be made for dimensional tolerance in handcrafted glasses.

**REV 10/24**




ORDERING:

FIXTURE	SHADE OPTIONS	LAMP OPTIONS	METAL FINISH	OPTIONS
2SW 14.625" Vanity	565807 Opal Matte	(blank) 40W G9 Socket	BR Bronze	SQ Square
3SW 22.5" Vanity	565819 Carrera	LED 5W LED 120V, dimmable	SN Satin Nickel	Canopy

**Ex. 3SW-565819-SN**  
 Palla 5 3-Light Vanity w/  
 Carrera Glass Shades, Satin  
 Nickel Finish

*\*LED is replaceable  
 source, 90+ CRI,  
 3000°K CCT, 450  
 lumens, 25,000  
 hours.*

*\*This finish is not available  
 in 2SW and 3SW*



2SW: 14.625" L



3SW: 22.5" L



Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

Project Information: