

# ΚΟΝΑ

# VANITIES WALL

# **SPECIFICATIONS:**

#### DESCRIPTION

2-3 light vanity luminaires featuring handcrafted glass.

### LAMPING

**Standard:** 40W G9 Bi-pin base, 120V, lamp included. Suitable for use in an open fixture. Dimmable with standard incandescent dimmer (not included). **LED:** 5W Replaceable source, 120V, dimmable, 90+ CRI, 3000° K CCT, 450 lumens, 25,000 hours, lamp included.

#### DIFFUSER

Shade shall be handcrafted glass of various decors. 5.5" Dia. x 2.5" H, spaced 7.875" apart on center.

#### CONSTRUCTION

Fixture utilizes metal arm assembly and stamped steel body, with plated finish. Decorative finials can be removed for downlighting applications. Decorative outlet box cover optional when not required.

### **METAL FINISH**

Fixture shall be finished in Bronze or Satin Nickel.

#### MOUNTING

Installs directly to a 4" octagonal outlet box, with 1.75" left or right offset. Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

## LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



#### KONA SHOWN IN WHITE STARPOINT (282453) WITH SQUARE CANOPY



### For ordering information, see next page

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.




## **ORDERING:**

FIXTURE -	SHADE OPTIONS	- LAMP OPTIONS	- METAL FINISH - OPTIONS
2SW 14.625" Vanity 3SW 22.5" Vanity	117607 White   117652 Marble   117681 Sunset   117691 Bi-color   282453 White Starpoint   282484 Blue Starpoint   282490 Mango Starpoint	(blank) 40W G9 Socket LED 5W LED 120V, dimmable * LED is replaceable source, 90+ CRI, 3000°K CCT, 450 lumens, 25,000 hours.	BR Bronze SQ Square SN Satin Nickel Canopy

#### Ex. 3SW-282453-SN

Kona 3-Light Vanity w/ White Starpoint Glass Shades, Satin Nickel Finish



2SW: 14.625" L



3SW: 22.5" L



Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

**Project Information:**