

TAY TAY

VANITIES WALL

location:

SPECIFICATIONS:

DESCRIPTION

2-3 light vanity luminaires featuring handcrafted glass.

LAMPING

Standard: 40W G9 Bi-pin base, 120V, lamp included. Suitable for use in an open fixture. Dimmable with standard incandescent dimmer (not included). **LED:** 5W Replaceable source, 120V, dimmable, 90+ CRI, 3000° K CCT, 450 lumens, 25,000 hours, lamp included.

DIFFUSER

Shade shall be handcrafted glass of various decors. 4.125" Dia. x 3.875" H, spaced 7.875" apart on center.

CONSTRUCTION

Fixture utilizes metal arm assembly and stamped steel body, with plated finish. Decorative finials can be removed for downlighting applications. Decorative outlet box cover optional when not required.

METAL FINISH

Fixture shall be finished in Bronze or Satin Nickel.

MOUNTING

Installs directly to a 4" octagonal outlet box, with 1.75" left or right offset. Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



TAY TAY SHOWN IN CARRERA (560519) IN DOWNWARD ORIENTATION



For ordering information, see next page





ORDERING:

FIXTURE -	SHADE OPTIONS	 LAMP OPTIONS 	- METAL FINISH -	OPTIONS
2SW 14.625" Vanity 3SW 22.5" Vanity	560507 Opal Matte 560518 Amber Cloud 560519 Carrera	(blank) 40W G9 Socket LED 5W LED 120V, dimmable	BR Bronze SN Satin Nickel	SQ Square Canopy
	560586 Blue Cloud 5605HN Honey 5605RC Red Cloud	* LED is replaceable source, 90+ CRI, 3000°K CCT, 450 lumens, 25,000 hours	*This finish is not available in 2SW and 3SW	



Tay Tay 3-Light Vanity w/ Opal Matte Glass Shades, Satin Nickel Finish

Ex. 3SW-560507-SN





Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.