



NICO 4

VANITIES WALL

location:
DAMP

SPECIFICATIONS:

DESCRIPTION

2-3 light vanity luminaires featuring handcrafted glass.

LAMPING

Standard: 40W G9 Bi-pin base, 120V, lamp included. Suitable for use in an open fixture. Dimmable with standard incandescent dimmer (not included).

LED: 5W Replaceable source, 120V, dimmable, 90+ CRI, 3000° K CCT, 450 lumens, 25,000 hours, lamp included.

DIFFUSER

Shade shall be handcrafted glass of various decors.
3.5" Dia. x 3.75" H, spaced 7.875" apart on center.

CONSTRUCTION

Fixture utilizes metal arm assembly and stamped steel body, with plated finish. Decorative finials can be removed for downlighting applications. Decorative outlet box cover optional when not required.

METAL FINISH

Fixture shall be finished in Bronze or Satin Nickel.

MOUNTING

Installs directly to a 4" octagonal outlet box, with 1.75" left or right offset. Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



NICO 4 SHOWN IN GLITTER (5125GL) WITH SQUARE CANOPY IN DOWNWARD ORIENTATION

5125CF
STONE COPPER FOIL



5125GF
STONE GOLD FOIL



512500
CLEAR STONE



5125SF
SILVER FOIL



For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/24




ORDERING:

FIXTURE	-	SHADE OPTIONS	-	LAMP OPTIONS	-	METAL FINISH	-	OPTIONS
2SW 14.625" Vanity		512500 Clear Stone		(blank) 40W G9 Socket		BR Bronze		SQ Square
3SW 22.5" Vanity		5125CF Stone Copper Foil		LED 5W LED 120V, dimmable		SN Satin Nickel		Canopy
		5125GF Stone Gold Foil						
		5125GL Glitter Stone						
		5125SF Stone Silver Foil						

Ex. 3SW-512500-SN

Nico 4 3-Light Vanity w/ Clear Stone Glass Shades, Satin Nickel Finish

** LED is replaceable source, 90+ CRI, 3000°K CCT, 450 lumens, 25,000 hours.*



2SW: 14.625" L



3SW: 22.5" L



Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

Project Information: