

# ΜΙΑ

# VANITIES WALL

# **SPECIFICATIONS:**

#### DESCRIPTION

2-3 light vanity luminaires featuring handcrafted glass.

## LAMPING

**Standard:** 40W G9 Bi-pin base, 120V, lamp included. Suitable for use in an open fixture. Dimmable with standard incandescent dimmer (not included). **LED:** 5W Replaceable source, 120V, dimmable, 90+ CRI, 3000° K CCT, 450 lumens, 25,000 hours, lamp included.

#### DIFFUSER

Shade shall be handcrafted glass of various decors. 5.0" Dia. x 4.5" H, spaced 7.875" apart on center.

#### CONSTRUCTION

Fixture utilizes metal arm assembly and stamped steel body, with plated finish. Decorative finials can be removed for downlighting applications. Decorative outlet box cover optional when not required.

#### **METAL FINISH**

Fixture shall be finished in Bronze or Satin Nickel.

#### MOUNTING

Installs directly to a 4" octagonal outlet box, with 1.75" left or right offset. Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

## LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



MIA SHOWN IN OPAL MATTE (177907) IN BLACK FINISH



#### For ordering information, see next page


All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses. location:



## **ORDERING:**

**Ex. 3SW-177919-SN** Mia 3-Light Vanity w/ Carrera Glass Shades, Satin Nickel Finish

FIXTURE -	SHADE OPTIONS	- LAMP OPTIONS	- METAL FINISH	- OPTIONS
<b>2SW</b> 14.625" Vanity <b>3SW</b> 22.5" Vanity	177907 Opal Matte   177918 Amber Cloud   177919 Carrera   177948 Blue Cloud   17794B Habanero   1779HA Honey   1779MA Magma   1779MC Marble Grigio   1779MC Red Cloud	(blank) 40W G9 Socket LED 5W LED 120V, dimmable * LED is replaceable source, 90+ CRI, 3000°K CCT, 450 lumens, 25,000 hours.	BR Bronze SN Satin Nickel	<b>SQ</b> Square Canopy





3SW: 22.5" L



Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

**Project Information:**