

AERO 16 / 21

SCONCES WALL



DESCRIPTION

Wall-mounted ADA-compliant sconces featuring open-ended handcrafted glass.

LAMPING

Standard: 60W MAX E26 base A15, 120V, suitable for dimming, lamp not included. (Incandescent dimmer is suitable for dimming, not included) LED: 5W LED Replaceable source 120V, CL dimmable, 90+ CRI, 3000°K CCT, 550 lumens, 30,000 hours, lamp included. (Aero 16 only) LED: 9W LED Replaceable source 120V, CL dimmable, 90+ CRI, 3000°K CCT, 800 lumens, 30,000 hours, lamp included. (Aero 21 only)

DIFFUSER

Diffuser shall be handcrafted glass of various decors. Aero 16: 4.5" W x 15.5" H x 4" D **Aero 21:** 4.5" W x 21.25" H x 4" D

CONSTRUCTION

Steel fitter and canopy-cover available with plated finishes. Glass is secured by steel set screws.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture. 75°C supply wire required for incandescent lamping. Orient horizontal or vertical, wall-mount only.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



AERO 21 SHOWN IN STUCCO (2729ST)

ORDERING:

Aero 16: #2728	Aero 21: #2729	FIXTURE/DECOR 272807 Opal Matte 2728ST Stucco	- LAMP OPTIONS (blank) 2x 60W A15 LED 2x SW LED 120V	- METAL FINISH BK Black BR Bronze PN Polished Nickel SN Satin Nickel	- OPTIONS LW Low Wattage labeling
		FIXTURE/DECOR 272907 Opal Matte 2729ST Stucco	Aero 16	- METAL FINISH BK Black BR Bronze PN Polished Nickel SN Satin Nickel 728ST-SN Wall Sconce w/ Stuickel Finish	- OPTIONS LW Low Wattage labeling
Project Information:		All dimen:	sions provided are nominal.		

ADA

COMPLIANT