

KILLIAN 26



SPECIFICATIONS:

DESCRIPTION

Wall-mounted **ADA-compliant** sconces featuring closed-ended handcrafted glass.

LAMPING

Standard: 3x 40W G9 Halogen 120V, suitable for dimming, lamp included. **LED:** 3x 9W LED Replaceable source 120V, CL dimmable, 90+ CRI, 3000°K CCT, 800 lumens, 30,000 hours, lamp included.

DIFFUSER

Diffuser shall be handcrafted Satin White glass.

CONSTRUCTION


Steel fitter with white powder coat finishes. Glass is secured by steel set screws.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture. 75°C supply wire required for incandescent lamping. Orient horizontal or vertical, wall-mount only.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).





ORDERING:

| FIXUTRE/DECOR | - LAMP OPTIONS | - METAL FINISH | |
|-----------------------|---------------------------|-----------------|--|
| KILLIAN26 Satin White | (blank) 3x 40W G9 Sockets | CR Chrome | |
| | IFD 3x 9W LFD | SN Satin Nickel | |

Ex. KILLIAN26-SW-CR

Killian 26 Wall Sconce w/ Satin White Glass, Chrome Finish

| Project Information: | | |
|----------------------|--|--|
| | | |
| | | |
| | | |
| | | |

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/24