

DARCI 16 / 21



location: DAMP

SCONCES WALL

SPECIFICATIONS:

DESCRIPTION

Wall-mounted **ADA-compliant** sconces featuring open-ended handcrafted glass.

LAMPING

Standard: 60W E26 base A15, 120V, suitable for dimming, lamp not included. (*Incandescent dimmer is suitable for dimming, not included*)

LED: 5W LED Replaceable source 120V, CL dimmable, 90+ CRI, 3000°K CCT, 550 lumens, 30,000 hours, lamp included. (Darci 16 only)

LED: 9W LED Replaceable source 120V, CL dimmable, 90+ CRI, 3000°K CCT, 800 lumens, 30,000 hours, lamp included. (Darci 21 only)

DIFFUSER

Diffuser shall be handcrafted glass of Opal Matte decor.

Darci 16: 4.75" W x 15.5" H x 3.625" D **Darci 21:** 4.75" W x 21.25" H x 3.625" D

CONSTRUCTION

Steel fitter and canopy-cover available with plated finishes. Glass is secured by steel set screws.

METAL FINISH

Decorative metal accents shall be in various finish options.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture. 75°C supply wire required for incandescent lamping. Orient horizontal or vertical, wall-mount only.


LABELS


UL or ETL Listed. Suitable for Damp Locations (interior use only).

DARCI 16 SHOWN IN OPAL MATTE (272507) & DARCI 21 SHOWN IN OPAL MATTE (272607)

OPTIONS

ORDERING:





TIXTORL/DECOR	LAMIT OF HORS	MEINLINISII	01 110113
272507 Opal Matte	(blank) 2x 60W A15	BK Black	LW Low Wattage
	LED 2x 5W LED 120V	BR Bronze	labeling
		PN Polished Nickel	
		SN Satin Nickel	
FIXTURE/DECOR	- LAMP OPTIONS	- METAL FINISH -	OPTIONS
272607 Opal Matte	(blank) 3x 60W A15	BK Black	LW Low Wattage
	LED 2x 9W LED 120V	BR Bronze	labeling
		PN Polished Nickel	

I AMP OPTIONS

Ex. 272507-SN

Darci 16 Wall Sconce w/ Opal Matte Glass, Satin Nickel Finish

- METALFINISH -

Project Information	1:		

All dimensions provided are nominal.

Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/24

FIXTURE/DECOR -