



# OPTOS

SCONCES WALL

location:  
**DAMP**

## SPECIFICATIONS:

### DESCRIPTION

Accent lighting sconce with dual lenses, lens unit swivels 359° where it attaches to the canopy.

### LAMPING

**Standard:** 40W G9 Bi-pin socket, 120V, lamp included.

Lamps are suitable for use in an open fixture.

**LED:** 5W LED Replaceable source 120V, CL dimmable, 90+ CRI, 3000°K CCT, 450 lumens, 25,000 hours, lamp included.

### LENSES

3.5" Diameter. Domed flood light glass lenses are available in combinations. Options include Clear and Frost.

### CANOPY

Canopy (4.375" Sq.) and Faceplate (5") is plated metal.

### METAL FINISH


Canopy and lens unit hardware shall be finished in Chrome or Brushed Aluminum

### MOUNTING

Installs directly to a 4" junction box. Unit secures with concealed screws.

### LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



CL  
CLEAR

FR  
FROST

## ORDERING:

FIXTURE	LENS COMBINATION	LAMP OPTIONS	METAL FINISH
OPTOS1W Sconce	CLCL Clear/Clear CLFR Clear/Frost FRFR Frost/Frost	(blank) G9 Socket LED 5W LED 120V, dimmable	BA Brushed Alum. CR Chrome

**Ex. OPTOS1W-CLCL-BA**

Optos Wall Sconce w/ Clear and Clear Lens Combination,  
Brushed Aluminum Finish

**Project Information:**

All dimensions provided are nominal.  
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/24