



TAMBURO STONE

SCONCES WALL



location:
DAMP

SPECIFICATIONS:

DESCRIPTION

Wall-mounted **ADA-compliant** sconce featuring open-ended handcrafted glass.

LAMPING

Standard: 75W E26 base A19, 120V, suitable for dimming. Lamp not included. *(Incandescent dimmer is suitable for dimming, not included)*

LED: 8W LED Replaceable source 120V, CL dimmable, 90+ CRI, 3000°K CCT, 800 lumens, 30,000 hours, lamp included.

DIFFUSER

Diffuser shall be handcrafted glass of various decors.

CONSTRUCTION

Glass is secured to the backplate by braided wire. Rectangular backplate (nominal 4" W x 6.5" H) shall be constructed of steel, powder-coated white.

METAL FINISH

Decorative metal accents shall be in various finish options.

MOUNTING


Installs directly to a 4" octagonal outlet box. 75°C supply wire required for incandescent lamping. Top of glass is approximately 6.125" above the outlet box centerline.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



TAMBURO 8 SHOWN IN STONE GOLD FOIL (7090GF) & STONE SILVER FOIL (7090SF)



ORDERING:

FIXTURE/DECOR	LAMP OPTIONS	METAL FINISH	OPTIONS
7090GF Stone Gold Foil	(blank) 75W A19	BK Black	LW Low
7090SF Stone Silver Foil	LED 8W LED 120V, dimmable	BR Bronze	Wattage labeling
		PN Polished Nickel	
		SN Satin Nickel	
		WH White	

Ex. 7090SF-SN

Tamburo Stone Wall Sconce w/ Silver Stone Foil Glass, Satin Nickel Finish

Project Information:

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/24