

# CIRRUS



# location:

## **SPECIFICATIONS:**

#### **DESCRIPTION**

Wall-mounted **ADA-compliant** sconce featuring handcrafted glass diffuser is enclosed on top to conceal lamp if viewed from above.

#### **LAMPING**

Standard: 75W E26 base A19, 120V, lamp not included. Dimmable with standard incandescent dimmer (not included). LED: 8W Replaceable LED source, 120V, CL dimmable, 90+ CRI, 3000°K CCT, 800 lumens, 30,000 hours, lamp included.

#### **DIFFUSER**

Diffuser shall be of glass in Opal Matte, Gold or Black decors.


#### **CONSTRUCTION**

Half circle shaped, stamped aluminum fitter (9" L x 4.625" H x 0.75" D) is powder coated white. Glass secured by stainless steel set screws.

#### **MOUNTING**

Installs directly to a 4" octagonal outlet box. 75°C supply wire required for incandescent lamping. Fixture is centered on the outlet box.

UL or ETL Listed. Suitable for Wet Locations (interior or exterior use).





CIRRUS SHOWN IN OPAL MATTE (297107)

2971GD

GOLD



2971BK


BLACK

### **ORDERING:**

FIXTURE	- LAMP OPTIONS
<b>297107</b> Opal Matte	(blank) 1x 75W A19
2971BK Black	LED 1x 8W LED 120V,
2971GD Gold	dimmable

### Ex. 297107

1 Lt. Cirrus Sconce w/ Opal Matte Glass, White Finish





All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

**REV 10/24**