



TOMAS

SCONCES WALL



SPECIFICATIONS:

DESCRIPTION

Wall-mounted **ADA-compliant** sconce featuring open-ended handcrafted glass.

LAMPING

Standard: 75W A19 120V incandescent, suitable for dimming. lamp not included. *(Incandescent dimmer is suitable for dimming, not included)*

LED: 8W LED Replaceable source 120V, CL dimmable, 90+ CRI, 3000°K CCT, 800 lumens, 30,000 hours, lamp included.

DIFFUSER

Diffuser shall be handcrafted glass of various decors.

CONSTRUCTION

Glass is secured to the backplate by braided wire. Rectangular backplate (nominal 4" W x 6.5" H) shall be constructed of steel, powder-coated white.

METAL FINISH


Decorative metal accents shall be in various finish options.

MOUNTING

Installs directly to a 4" octagonal outlet box. 75°C supply wire required for incandescent lamping. Top of glass is approximately 3.5" above the outlet box centerline.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



TOMAS SHOWN IN AMBER MATTE (704180) & RUBY MATTE (7041RM)

704107
OPAL MATTE

7041VM
VANILLA MATTE

7041CM
COBALT BLUE MATTE



ORDERING:

FIXTURE/DECOR	LAMP OPTIONS	METAL FINISH	OPTIONS
704107 Opal Matte	(blank) 75W A19 Incan	BK Black	LW Low
704180 Amber Matte	LED 8W LED 120V,	BR Bronze	Wattage
7041CM Cobalt Blue Matte	dimnable	PN Polished Nickel	Labeling
7041RM Ruby Matte		SN Satin Nickel	
7041VM Vanilla Matte		WH White	

Ex. 704180-SN
Tomas Wall Sconce w/ Amber Matte Glass,
Satin Nickel Finish

Project Information:

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 12/18