

CIRO

VANITIES WALL





SPECIFICATIONS:

DESCRIPTION

2-4 Light **ADA-compliant** vanity luminaires featuring handcrafted glass.

IAMPING

Standard: 50W G9 Halogen 120V, suitable for dimming, lamp included. **LED:** 5W Replaceable source, 120V, dimmable, 90+ CRI, 3000° K CCT, 450 lumens, 25,000 hours, lamp included.

DIFFUSER

Diffuser shall be handcrafted Opal Matte glass. 6.375" Dia., spaced 7.875" on center.

CONSTRUCTION

Rectangular canopy (4.75" x 5.5" H) and lampholder are stamped steel, with plated finish.

METAL FINISH

Fixture shall be finished in Bronze, Chrome or Satin Nickel.

MOUNTING

Installs directly to a 4" octagonal outlet box, with up to 1" offset. Orient horizontal or vertical, wall-mount only.

IARFIS

UL or ETL Listed. Suitable for Damp Locations (interior use only).





CIRO SHOWN IN OPAL MATTE (773807) IN CHROME FINISH

ORDERING:

FIXTURE	DECOR	- LAMPING OPTIONS	- METAL FINISH
1WS Sconce	773807 Opal Matte	(blank) 50W G9 Hal	BR Bronze
2WS 2 Light		LED 5W LED 120V,	CR Chrome
3WS 3 Light		dimmable	SN Satin Nickel
4WS 4 Light			

Ex. 3WS-773807-SN Ciro Vanity w/ Opal Matte Glass, Satin Nickel Finish





2WS: 14.625" L x 6.375" H x 3.5" D

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 12/18