



CHELSEA

SCONCES WALL



SPECIFICATIONS:

DESCRIPTION

Wall-mounted **ADA-compliant** sconce featuring open-ended handcrafted glass.

LAMPING

Standard: 75W A19 120V incandescent, suitable for dimming, lamp not included. *(Incandescent dimmer is suitable for dimming, not included)*

LED: 8W LED Replaceable source 120V, CL dimmable, 90+ CRI, 3000°K CCT, 800 lumens, 30,000 hours, lamp included.

DIFFUSER

Diffuser shall be handcrafted glass of various decors.

CONSTRUCTION

Glass is secured to the backplate by braided wire. Rectangular backplate (nominal 4" W x 6.5" H) shall be constructed of steel, powder-coated white.

METAL FINISH


Decorative metal accents shall be in various finish options.

MOUNTING

Installs directly to a 4" octagonal outlet box. 75°C supply wire required for incandescent lamping. Top of glass is approximately 3.625" above the outlet box centerline.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



CHELSEA SHOWN IN AMBER CLOUD (704318) & HONEY (7043HN)

704307
OPAL MATTE

704319
CARRERA



ORDERING:

FIXTURE/DECOR	LAMP OPTIONS	METAL FINISH	OPTIONS
704307 Opal Matte	(blank) 75W A19 Incan	BK Black	LW Low Wattage
704318 Amber Cloud	LED 8W LED 120V,	BR Bronze	labeling
704319 Carrera	dimmmable	PN Polished Nickel	
7043HN Honey		SN Satin Nickel	
		WH White	

Ex. 7043HN-SN
Chelsea Wall Sconce w/ Honey Glass,
Satin Nickel Finish

Project Information:

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 12/18