



NICO 4

VANITIES WALL

location:
DAMP

SPECIFICATIONS:

DESCRIPTION

2-4 light vanity luminaires featuring handcrafted glass.

LAMPING

Standard: 40W Low-pressure G9 Halogen, 120V, lamp included. Suitable for use in an open fixture. Dimmable with standard incandescent dimmer (not included).

LED: 5W Replaceable source, 120V, dimmable, 90+ CRI, 3000° K CCT, 450 lumens, 25,000 hours, lamp included.

DIFFUSER

Shade shall be handcrafted glass of various decors.
3.5" Dia. x 3.75" H, spaced 7.875" apart on center.

CONSTRUCTION

Fixture utilizes metal arm assembly and stamped steel body, with plated finish. Decorative finials can be removed for downlighting applications. Decorative outlet box cover optional when not required.

METAL FINISH

Fixture shall be finished in Bronze, Chrome or Satin Nickel.

MOUNTING

Installs directly to a 4" octagonal outlet box, with 1.75" left or right offset. Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



NICO 4 SHOWN IN GLITTER (5125GL) WITH SQUARE CANOPY IN DOWNWARD ORIENTATION

5125CF
STONE COPPER FOIL



5125GF
STONE GOLD FOIL



512500
CLEAR STONE



5125SF
SILVER FOIL



For ordering information, see next page


All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 8/21



ORDERING:

FIXTURE	-	GLASS OPTIONS	-	METAL FINISH	-	METAL FINISH	-	OPTIONS
2SW	2 Light Vanity	512500	Clear Stone	(blank)	40W G9 Hal	BR	Bronze	SQ Square Canopy
3SW	3 Light Vanity	5125CF	Stone Copper Foil	LED	5W LED 120V, dimmable	CR	Chrome	
4SW	4 Light Vanity	5125GF	Stone Gold Foil			SN	Satin Nickel	
		5125GL	Glitter Stone					
		5125SF	Stone Silver Foil					



Ex. 3SW-51250S-SN

Nico 4 3-Light Vanity w/ Opal Stone Glass, Satin Nickel Finish

2SW: 14.625" L



3SW: 22.5" L



4SW: 30.375" L



Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

Project Information: