



PRIMO 11 / 14

FLUSH MOUNT CEILING

location:
DAMP

SPECIFICATIONS:

DESCRIPTION

Flush-mounted ceiling fixture, featuring Opal Matte glass diffuser.

LAMPING

LED: 17W Integrated source, 120V, CL dimmable, 90+ CRI, 3000°K CCT, 1200 lumens, 30,000 hours, included. (Primo 11 only)

LED: 28W Integrated source, 120V, CL dimmable, 90+ CRI, 3000°K CCT, 2160 lumens, 30,000 hours, included. (Primo 14 only)

DIFFUSER

Handcrafted glass diffuser in Opal Matte.

Primo 11: 11.5" Dia. x 3.25" H

Primo 14: 14" Dia. x 3.75" H

CONSTRUCTION

Glass diffuser is secured to fitter with three set screws. Stamped aluminum fitter is powder coated white.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture.

90°C supply wire required for incandescent lamping.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



OPAL MATTE

Project Information:


All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 12/18




ORDERING:

Primo 11: _____



FIXTURE OPTIONS	-	LAMP OPTIONS
PRIMO11C 11.5" Opal Matte		LED 17W LED, 1200 lumens

Primo 14: _____



FIXTURE OPTIONS	-	LAMP OPTIONS
PRIMO14C 14" Opal Matte		LED 28W LED, 2160 lumens

Ex. PRIMO11C-LED
Primo 11 Ceiling, Opal Matte Shade

Project Information: