



VIVA 13 / 16

FLUSH MOUNT CEILING

location:
DAMP

SPECIFICATIONS:

DESCRIPTION

Flush-mounted ceiling fixture, featuring Opal glass with patterned Clear center diffuser.

LAMPING

LED: 16W Integrated source, 120V, CL dimmable, 90+ CRI, 3000°K CCT, 1500 lumens, 30,000 hours, included. (Viva 13 only)

LED: 24W Integrated source, 120V, CL dimmable, 90+ CRI, 3000°K CCT, 2500 lumens, 30,000 hours, included. (Viva 16 only)

DIFFUSER

Handcrafted glass diffuser in Opal with patterned Clear center .

Viva 13: 13" Dia. x 4" H

Viva 16: 16" Dia. x 4.5" H

CONSTRUCTION

Glass diffuser is secured to fitter with "twist & lock" bayonet action. Stamped aluminum fitter is powder coated white.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture.
90°C supply wire required for incandescent lamping.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



OPAL/CLEAR

Project Information:


All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 12/18




ORDERING:

Viva 13: _____



FIXTURE OPTIONS	-	LAMP OPTIONS
VIVA13C 13" Opal/Clear		LED 16W LED 1500 lumens

Viva 16: _____



FIXTURE OPTIONS	-	LAMP OPTIONS
VIVA16C 16" Opal/Clear		LED 24W LED 2500 lumens

Ex. VIVA13C-LED
Viva 13 Ceiling, Opal/Clear Shade,

Project Information: