



BLINK

SCONCES OUTDOOR

location:
WET

SPECIFICATIONS:

DESCRIPTION

Wall-mounted sconces featuring handcrafted glass.

LAMPING

Standard: 60WT10 Medium-based 120V incandescent, lamp not included. Dimmable with standard incandescent dimmer (not included).

LED: 4W Replaceable 120V LED GU10, dimmable, 82+ CRI, 3000°K CCT, 240 lumens, 25,000 hours, lamp included.

LED Filament: 4W Replaceable T-shape LED Filament lamp, 120V, dimmable, 90+ CRI, 3000°K CCT, 350 lumens, 15,000 hours, lamp included.

DIFFUSER

Diffuser shall be handcrafted glass of various decors. 4.375" Dia. x 8" H

CONSTRUCTION

Cast Aluminum bracket powdered-coated in Black, Silver or White finish. Glass secured by set screws.

MOUNTING


Installs directly to a 4" octagonal outlet box. May be used in either upward or downward orientation in indoor applications, downward only for outdoor. 75°C supply wire required for incandescent lamping.

LABELS

UL or ETL Listed. Suitable for Wet Locations (interior or exterior use).



BLINK SHOWN IN BLUE/CLEAR (BLINKBL) & IN CLEAR (BLINKCL)



BLINKSM
SMOKE/CLEAR

BLINKAM
AMBER/CLEAR



ORDERING:

FIXTURE/DECOR	LAMP OPTIONS	METAL FINISH
BLINKAM-WALL Amber/Clear	(blank) 60WT10 Incan	BK Black
BLINKBL-WALL Blue/Clear	EDIL 4W LED Filament	SL Silver
BLINKCL-WALL Clear	LED 4W LED	WH White
BLINKSM-WALL Smoke/Clear		

Ex. BLINKAM-WALL-BK
Blink Sconce w/ Smoke/Clear Glass,
Black Finish

Project Information:

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 8/21